Phone: - Email:

UTEPO, 8 Ports Industrial Full Gigabit PoE Managed Switch



Marca:

Código del producto: 1683, UTP7308GE-PoE

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

UTP7308GE-POE is 8 Ports Industrial Full Gigabit PoE Managed SwitchProvide 8* 10/100/1000Base-T Ethernet ports(PoE), 4 * 1000BASE-X SFP ports(Unlinks). The switch provides up to 4Mbit cache, Support 4K high-definition video transmission. Besides, the 8 downlink PoE ports support IEEE802.3af/at standard. PoE output power of single port is up to 60W

Descripción

Model Number

Downlink Ports
Uplink Ports

Network Standard

UTP7308GE-POE

8* 10/100/1000Base-T PoE RJ45 ports

4*1000Base-X SFP ports

IEEE802.3 ?IEEE802.3u?IEEE802.3ab?IEE

E802.3Z?IEEE802.3X? IEEE 802.1Q IEEE 802.1p IEEE 802.3ad ?IEEE

802.1D?IEEE 802.1X

24Gbps

18Mpps

Storage& Transfer

4M

8K

802.3af/at End-span

1/2(+)?3/6(-)

Bandwidth

Packet Transfer Rate

Exchange Way

Buffer

MAC Address

PoE Standard
PoE Power Supply

PoE Line Pair

PoE Output Sigle Port ? 30W PoE

alarm signal output by relay Support relay alarm for power off, ports

network link-off, ports PoE off? Set by

Web Software?

Surge Immunity 6KV Per: IEC61000-4-5

ESD Protection ESD Level 4 Per: IEC61000-4-2

RS Level 4 Per: IEC61000-4-3

EFT Level 4 Per: IEC61000-4-4

CS Level 4 Per: IEC61000-4-6

Input Voltage 48~57V DC

Power Consumption Self consumption?15W

Operation Temperature -40?~75? **Storage Temperature** -40?~85?

Operation Humidity 5%-95%?no-condensation? **Dimension(LxWxH)** 159mm×110mm×46.5mm

Weight 1kg

Authentication CE?FCC?ROHS

Software Parameter?

Port Management Support Port Enable/Disable;

Support Port Rate Settings;

Support Port Full-duplex Mode; Support IEEE802.3x Flow Control;

Support Port Name Change;

VLAN Support 4K VLAN

Support 802.1Q Protocol-Based VLAN;

Support Port-Based VLAN;

QoS Support QoS;

Support 8-Level Priority management for

switching;

Support WRR;

Support 820.1P and DSCP Priority;

Multicast Management Support SNMP V1/V2/V3 Protocol;

Support IGMP Snooping;

POE Management Support Total Power Consumption Control;

Support PoE ON/OFF;

Support Single Port 60W/30W max. Power

Change and Port Output Priority;

alarm signal output by relay Support relay alarm for power off, ports network link-off, ports PoE off Support IP?MAC?Port?VLAN Combination **Safety Character** and Binding; Support MAC address auto-learning, aging& filter; Support Port Isolation, Port Speed-Limited; Support RSTP; Support Fast-Ring; Support 5 groups of 8-Port trunk; Support RADIUS Authentication & 802.1X Authentication; Support WEB Management, CLR Settings **System Management& Maintenance** and telnet Settings; Support CLR Settings; Support Flow Calculate;

Support CLR Settings;
Support FTP/TFTP/HTTP Web Upgrading;
Support Flow Calculate;
Support MAC address Form Search;
Support IP Address, DNS Server Change
Support Username& Password Change;
Support History Record, Journal
management;

Support System settings Backup;